



One Machine - One Operator - Endless Applications



CX 55 SPECIFICATION


- ◆ Engine: Kohler, 55 hp (1.9 litre)
- ◆ Emissions class: Tier 4 final
- ◆ Length: 3490 mm (137.4 in)
- ◆ Width: 1150 - 1560 mm (45 - 61.5 in)
- ◆ Height: 1980 - 2040 mm (78 - 80 in)
- ◆ Wheelbase: 1710 mm (67 in)
- ◆ Unladen weight: 1950 - 2300 kg (4299 - 5071 lb)
- ◆ Axle capacity, front: 2300 kg (5071 lb)
- ◆ Axle capacity, rear: 2500 kg (5512 lb)
- ◆ Gross vehicle weight: 3500 kg (7716 lb)
- ◆ Outer turning radius: 2663 - 2863 mm (105 - 113 in)
- ◆ Maximum speed: 40 km/h (25 mph)
- ◆ Load-sensing PTO hydraulics front & rear, with optional front mechanical PTO
- ◆ Hydraulic flow up to 100 litres (26.4 gal), operating pressure up to 220 bar (3190 psi)



CX 55 L / CX 75 SPECIFICATION

- ◆ Engine: Kohler, 55/75 hp (1.9/2.5 litre)
- ◆ Emissions class: Tier 4 final
- ◆ Length: 3680 mm (145 in)
- ◆ Width: 1150 - 1560 mm (45 - 61.5 in)
- ◆ Height: 1980 - 2040 mm (78 - 80 in)
- ◆ Wheelbase: 1900 mm (75 in)
- ◆ Unladen weight: 2200 - 2500 kg (4850 - 5512 lb)
- ◆ Axle capacity, front: 2500 kg (5512 lb)
- ◆ Axle capacity, rear: 2500 kg (5512 lb)
- ◆ Gross vehicle weight: 3500 - 4000 kg (7716 - 8818 lb)
- ◆ Outer turning radius: 2938 - 3134 mm (115 - 123 in)
- ◆ Maximum speed: 40 km/h (25 mph)
- ◆ Load-sensing PTO hydraulics front & rear, with optional front mechanical PTO
- ◆ Hydraulic flow up to 100 litres (26.4 gal), operating pressure up to 220 bar (3190 psi)

Your local authorised dealer is:



- 🏠 Multihog Global Headquarters, Finnabair Business Park, Dundalk, Co. Louth, Ireland.
- ✉ info@multihog.com
- ☎ +353 42 9386738 / 443 852 1842 (US/CA)
- 🌐 www.multihog.com



CX RANGE

Features & Technical Specification

CX RANGE THE FEATURES



- 1 Heavy duty tractor, ideal for snow clearing, grass mowing, sweeping, pressure washing and much more.
- 2 55 - 75 hp Kohler engine, meeting tier 4 final emissions standards without requiring a particulate filter.
- 3 Ergonomic joystick-controlled hydraulics for easy operation.

- 4 Spring and damper suspension for smooth drive and ultimate operator comfort.
- 5 Articulated body with compact width for easy operation on sidewalks and in narrow areas.
- 6 EU type-approved tractor with gross vehicle weight of 3500 - 4000 kg (7716 - 8818 lb).

POWER, COMFORT & INNOVATIVE DESIGN

