



STANDARD & HEAVY DUTY

# TrailKat

## Mowers



**TFR-HD 180**



**TK-120**

DURABILITY INNOVATION

COMMITMENT



Pivot Hitch



Safety Cover



Cast Pan  
Blade Carrier



WetCut available  
as option on all  
models



Offset Hitch

# Specifications

	TK-120	TK-180	TFR-HD120C	TFR-HD180C
Cutting Width	126"	180"	126"	180"
Overall Width	133"	187"	139"	190"
Overall Length	183"	183"	192"	192"
Transport Width, min	88"	96"	88"	88"
Deck Thickness	7GA (3/16")	7GA (3/16")	7GA (3/16")	7GA (3/16")
Weight (approx.)	4,800 lbs.	5,455 lbs.	5,100 lbs.	5,800 lbs.
Minimum PTO HP	60 HP	60 HP	50 HP	65 HP
Recommended PTO HP	75 HP	85 HP	75 HP	90 HP
Cutting Height	2" to 14"	2" to 14"	1.5 to 17.5"	1.5 to 17.5"
Ground Clearance	13.5"	13.5"	17.5"	17.5"
Cutting Capacity	4.5" Material	4.5" Material	4" Material	4" Material
Blade Overlap	6.0"	6.0"	6.5"	6.5"
Gear Box Warranty	6 year limited	6 year limited	5 year limited	5 year limited
Divider Gear Box Rating	250 HP	250 HP	260 HP	260 HP
Center/Wing Gearbox Rating	225 HP	225 HP	210 HP	210 HP
Blade Tip Speed	540 PTO RPM	540 PTO RPM	540 PTO RPM	540 PTO RPM
Center	16,286 ft/min	16,286 ft/min	15,981 ft/min	15,981 ft/min
Wing	16,422 ft/min	16,422 ft/min	15,493 ft/min	15,493 ft/min
Wing Working Range	25° down to 90° up	25° down to 90° up	25° down to 90° up	25° down to 90° up
Walking Axle Center	Optional	Optional	Standard	Standard
Walking Axles Wings	Available option	Available option	Available option	Available option
LED Light Kit	Standard	Standard	Standard	Standard
Required Tractor Remotes	2 Remotes	3 Remotes	2 Remotes	3 Remotes

# Specifications

## Tiger's Offset Hitch (TOH)

Allows the tractor to remain on the road while the mower is fully in the ditch.  
Provides operator safety and comfort with the ability to mow steep ditches without leaving the road.  
Attaches to 10" and 15" Trailkat mowers.

Tiger's Offset Hitch can be used with 540 or 1000 PTO

Swivel mounted gear boxes designed to keep drive shafts in line at all times.

Patented strut arm allows backing up like 2 wheel trailer.

Low center of gravity design provides visibility to cutter head.

Transport width is 102"

Machine weight 2,757 lbs.

Offset Hitch extends mower to the right rear of tractor.

Drive line rated at 136 hp.

Gear boxes rated at 200 hp continuous.

LED lights included.




The Tiger Trailkat pull behind mowers in 6' and 7' sizes that are designed to add flexibility, productivity and value to your tractor.

Built strong to handle your toughest mowing terrain with ease.

Fast and easy hook up with Tiger's 3 point hitch design, this mower can make quick work of your mowing and can disconnect when finished so tractor can be used for other work.

### SPECIFICATIONS

	TK-6	TK-7
Cutting Width	72"	84"
Overall Width	78"	88.5"
Overall Length	100"	130"
Deck Thickness	10 Ga	10Ga
Weight (approx.)	1,158 lbs.	1,350lbs.
Hitch	CAT I & QH	CAT I & QH
Gearbox Rating	130 HP	130 HP
Recommended PTO HP	45 HP	60 HP (Lift) 45 HP (Pull)
Cutting Height (Min)	1 1/2"	1 1/2"
Cutting Capacity (Max)	2"	2"
Side Skirt	10 Ga. x 9 1/4"	10 Ga. x 9 1/4"
Slip Clutch	Standard	Standard
Blade Tip Speed	16,286 ft/min	16,328 ft/min



### Dealer Info:



Tiger Corporation  
 3301 N. Louise Ave  
 Sioux Falls, SD 57107  
 800-843-6849  
[www.tigermowers.com](http://www.tigermowers.com)  
 An Alamo Group Company



MADE WITH PRIDE IN THE USA

Specifications are subject to change without notice. Optional equipment may be shown. One Year Warranty on all products.